

LED LAMP CATALOGUE



Commercial Projects using LED United LED Lamps - Lighting Design by Mr Resistor



Residential Projects using LED United LED Lamps - Lighting Design by Mr Resistor

REALITY CRI 80+ DIMMABLE LED LAMPS



GU10 7W
Page 3



GU10 5W
Page 4



GU11 4W
Page 5



GU10 AR70 7W
Page 6



ES111 12W
Page 7



PAR111 12W
Page 8



MR16 7W
Page 9



MODULE 10W
Page 10



MODULE 7W
Page 11



AR70 8W
Page 12



MR11 3.5W
Page 13



AR70 7W
Page 14



MR8 3W
Page 15



R7S 8W
Page 16

PRO REALITY CRI 90+ DIMMABLE LED LAMPS



GU10 9W
Page 19



GU10 5W
Page 20



MR16 9W
Page 21



PAR30 12W
Page 22



MODULE 15W
Page 23



MODULE 8W
Page 24



REALITY ATMOSPHERE DIM TO WARM LED LAMPS



GU10 8W
Page 27



GU10 5W
Page 28



MR16 8W
Page 29



AR70 8W
Page 30



AR111 12W
Page 31

LED GLASS GLASS LED LAMPS



GU10 5W
Page 33

LED **CONTRACT** ENCLOSED FITTING LED LAMPS



GU10 6W
Page 35



GU10 COLOUR
Page 36

Dynamic White LED MODULES



MODULE 8.5W
Page 38



MODULE 6W
Page 39



MODULE 12W
Page 40



CONTROLS
Page 41-42

RGB+WHITE LED MODULES



GU10 6W
Page 44




CONTROLS
Page 45

REALITY


LED LAMPS

The Reality LED range has been designed in the UK. The idea was to create an LED that matched a halogen lamp in terms of light source and aesthetics. We achieved this by using a single Cree LED chip and building the reflector around it. The result is a light that gives that arc of light that we are all used to seeing with halogen.




We have used an improved circuit for the LED driver for smooth, flicker free dimming. We have fully tested dimming with Lutron and various dimmer modules.

They are our most powerful LED lamps yet, but with the benefit of being energy efficient, all complying to Part L regulations. The Lamps high lumen output make them ideal for lighting large spaces and high ceilings.



Reality GU10



Halogen GU10

REALITY

GU10 7W

Dimmable



- Replicates a halogen reflector
- LED positioned further back for anti-glare
- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Equivalent to 75W GU10 Halogen Lamp
- Lifetime of 25,000 hours
- Emergency option available
- Cree XLamp CXA1512 LED


Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
REAL GU10D INT24	7W	2700K	630	90	24°	80	GU10	Yes
REAL GU10D 24D	7W	3000K	630	90	24°	80	GU10	Yes
REAL GU10D CW24	7W	4000K	630	90	24°	80	GU10	Yes
REAL GU10D INT45	7W	2700K	630	90	45°	80	GU10	Yes
REAL GU10D 45D	7W	3000K	630	90	45°	80	GU10	Yes
REAL GU10D CW45	7W	4000K	630	90	45°	80	GU10	Yes

LED GU10 7W 24°

m	24°	lux 630lm
1	0.25	3808
2	0.49	952
3	0.74	423
4	0.99	238
5	1.23	152

LED GU10 7W 45°

m	45°	lux 630lm
1	0.40	1649
2	0.81	412
3	1.21	183
4	1.61	103
5	2.02	65



REALITY

GU10 5W

Dimmable



- Replicates a halogen reflector
- LED positioned further back for anti-glare
- Complies with Part L regulations
- Fully dimmable with leading edge dimmers
- Equivalent to 50W GU10 Halogen Lamp
- Lifetime of 25,000 hours
- Emergency option available
- Cree Chip

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
REAL RETRO5 W12D	5W	3000K	500	100	12°	80	GU10	Yes
REAL RETRO5 I24D	5W	2700K	500	100	24°	80	GU10	Yes
REAL RETRO5 W24D	5W	3000K	500	100	24°	80	GU10	Yes
REAL RETRO5 C24D	5W	4000K	500	100	24°	80	GU10	Yes
REAL RETRO5 I45D	5W	2700K	500	100	45°	80	GU10	Yes
REAL RETRO5 W45D	5W	3000K	500	100	45°	80	GU10	Yes
REAL RETRO5 C45D	5W	4000K	500	100	45°	80	GU10	Yes
REAL RETRO5 I60D	5W	2700K	500	100	60°	80	GU10	Yes
REAL RETRO5 W60D	5W	3000K	500	100	60°	80	GU10	Yes
REAL RETRO5 C60D	5W	4000K	500	100	60°	80	GU10	Yes

LED GU10 7W 24°


m	24°	lux 630lm
1	0.27	2754
2	0.54	688
3	0.81	306
4	1.09	172
5	1.36	110

LED GU10 7W 45°

m	45°	lux 630lm
1	0.46	987
2	0.93	246
3	1.39	109
4	1.86	61
5	2.32	39

LED GU10 5W 60°

m	60°	lux 500lm
1	0.79	741
2	1.58	185
3	2.37	82
4	3.16	46
5	3.96	30






REALITY

GU11 4W

Dimmable

- LED positioned further back for anti glare
- Complies with Part L regulations
- Fully dimmable with leading edge dimmers
- Equivalent to 35W GU10
- Fits GU10 lampholder
- Emergency option available

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
REAL GU11D INT	4W	2700K	280	70	35°	80	GU10	Yes
REAL GU11D W/W	4W	3000K	280	70	35°	80	GU10	Yes





REALITY

AR70 GU10 7W

Dimmable

- Replicates a halogen reflector
- LED positioned further back for anti-glare
- Complies with Part L regulations
- Fully dimmable with leading edge dimmers
- Equivalent to 75W GU10 Halogen Lamp
- Lifetime of 25,000 hours
- Cree LED


Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
REAL 70GU10D 15D	8W	3000K	680	85	15°	80	GU10	Yes
REAL 70GU10D 35D	8W	3000K	680	85	35°	80	GU10	Yes

LED AR70 GU10 8W 15°

m	15°	lux 680lm
1	0.19	5914
2	0.39	1478
3	0.58	657
4	0.77	369
5	0.96	236

LED AR70 GU10 8W 35°

m	35°	lux 680lm
1	0.44	1215
2	0.88	303
3	1.32	135
4	1.77	75
5	2.21	48



REALITY

ES111 12W

Dimmable




- Replicates halogen reflector
- LED positioned further back for anti glare
- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Equivalent to 75W AR111
- Fits GU10 lampholder
- Emergency option available

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
REAL ES111 35D	12W	2700K	900	75	38°	80	GU10	Yes

LED ES111 712 45°

m	45°	lux
1	0.44	2401
2	0.88	600
3	1.31	266
4	1.75	150
5	2.19	96





REALITY

PAR111 2W


Dimmable

- Replicates halogen reflector
- LED positioned further back for anti glare
- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Equivalent to 75W AR111
- Fits ES/E27 lampholder
- Emergency option available
- Dali option available

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
REALPAR111/10D/3	12W	2700K	900	75	10°	80	ES/E27	Yes

LED ES111 712 45°

m	45°	lux
1	0.44	2401
2	0.88	600
3	1.31	266
4	1.75	150
5	2.19	96



REALITY

MR16 7W

Dimmable or Switching




- Replicates halogen reflector
- LED positioned further back for anti glare
- Complies with Part L regulations
- Fully dimmable with leading edge dimmers
- Equivalent to 75W GU10
- Fits MR16 lampholder
- Emergency option available
- Dali option available

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
REAL MR16D INT24	7W	2700K	630	90	24°	80	GU10	Yes
REAL MR16D 24D	7W	3000K	630	90	24°	80	GU10	Yes
REAL MR16D CW24	7W	4000K	630	90	24°	80	GU10	Yes
REAL MR16D INT45	7W	2700K	630	90	45°	80	GU10	Yes
REAL MR16D 45D	7W	3000K	630	90	45°	80	GU10	Yes

MR16 Non Dimmable Retro

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
REALMR1624D WW	7W	3000K	630	90	24°	80	GU10	No
REALMR1660D WW	7W	3000K	630	90	60°	80	GU10	No
REALMR1660D CW	7W	4000K	630	90	60°	80	GU10	No

LED GU10 7W 24°			LED GU10 7W 45°		
m	24°	lux 630lm	m	45°	lux 630lm
1	0.32	2777	1	0.50	
2	0.63	694	2	0.99	
3	0.95	308		1.49	
4	1.27	173	4	1.98	74
5	1.59	111	5	2.48	47



REALITY

MODULE 10W

Dimmable



- Replicates halogen reflector
- LED positioned further back for anti glare
- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Equivalent to 100W GU10
- Fits 50mm Downlight
- Emergency option available
- Cree LED Chip


Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
REAL MODULE 24/I	10W	2700K	900	90	24°	80	-	Yes
REAL MODULE 24/W	10W	3000K	900	90	24°	80	-	Yes
REAL MODULE 24/C	10W	4000K	900	90	24°	80	-	Yes
REAL MODULE 45/I	10W	2700K	900	90	45°	80	-	Yes
REAL MODULE 45/W	10W	3000K	900	90	45°	80	-	Yes

LED MODULE 10W 24°

m	24°	lux 900lm
1	0.28	3343
2	0.55	836
3	0.83	371
4	1.11	208
5	1.39	133

LED MODULE 10W 45°

m	45°	lux 900lm
1	0.49	1338
2	0.98	334
3	1.48	148
4	1.97	83
5	2.46	53



REALITY

MODULE SHORT 7W

Dimmable




- Replicates halogen reflector
- LED positioned further back for anti glare
- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Equivalent to 100W GU10
- Lifetime of 25,000
- Fits 50mm Downlight
- Emergency option available

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
REAL 25MM 45/I	7W	2700K	650	93	45°	80	-	Yes
REAL 25MM 45/W	7W	3000K	650	93	45°	80	-	Yes
REAL 25MM 45/CW	7W	4000K	650	93	45°	80	-	Yes

LED MODULE 7W 45°

m	45°	lux
1	0.72	917
2	1.44	229
3	2.16	101
4	2.88	57
5	2.46	36



REALITY

AR70 8W

Dimmable



- Replicates halogen reflector
- LED positioned further back for anti glare
- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Equivalent to 75W AR70
- Fits SBC / B15 lampholder
- Emergency option available

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
REAL AR70 INT 12	8W	2700K	750	94	12°	80	SBC	Yes
REAL AR70 WW 12	8W	3000K	750	94	12°	80	SBC	Yes
REAL AR70 INT 24	8W	2700K	750	94	24°	80	SBC	Yes
REAL AR70 WW 24	8W	3000K	750	94	24°	80	SBC	Yes
REAL AR70 INT 36	8W	2700K	750	94	36°	80	SBC	Yes
REAL AR70 WW 36	8W	3000K	750	94	36°	80	SBC	Yes

LED AR70 8W 12°


m	12°	lux 750lm
1	0.16	13062
2	0.32	3265
3	0.49	1451
4	0.65	816
5	0.81	522

LED AR70 8W 24°

m	24°	lux 750lm
1	0.26	5893
2	0.53	1473
3	0.79	654
4	1.06	368
5	1.32	235

LED AR70 8W 36°

m	36°	lux 500lm
1	0.48	1217
2	0.97	304
3	1.45	135
4	1.93	76
5	2.42	48



REALITY

MR11 3.5W

Dimmable




- Replicates halogen reflector
- LED positioned further back for anti glare
- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Equivalent to 35W GU10
- Fits MR11 lampholder
- Emergency option available

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
REAL MR11D INT	3.5W	2700K	320	91	35°	80	GU4	Yes
REAL MR11D WARM	3.5W	3000K	320	91	35°	80	GU4	Yes
REAL MR11D COOL	3.5W	4000K	320	91	35°	80	GU4	Yes

LED MR11 3.5W 35°

m	35°	lux
1	0.46	827
2	0.92	206
3	1.37	91
4	1.83	51
5	2.29	33



REALITY

AR111 13W

Dimmable or Switching



- Replicates halogen reflector
- LED positioned further back for anti glare
- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Equivalent to 75W AR111
- Fits AR111 lampholder
- Emergency option available
- Dali option available

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
REAL AR111D INT	13W	2700K	950	73	24°	80	G53	Yes
REAL AR111D WW	13W	3000K	950	73	24°	80	G53	Yes
REAL AR111D C/W	13W	4000K	950	73	24°	80	G53	Yes

AR111 Dali


Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
REAL AR111 DALI2	13W	2700K	950	73	24°	80	G53	Yes
REAL AR111 DALI3	13W	3000K	950	73	24°	80	G53	Yes

AR111 Non Dimmable Retro

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
REAL AR111 INT	13W	2700K	950	73	24°	80	G53	No
REAL AR111 WW	13W	3000K	950	73	24°	80	G53	No

LED AR111 13W 24°

m	24°	lux
1	0.27	4222
2	0.55	1055
3	0.82	469
4	1.10	263
5	1.37	168



REALITY

MR8 3W Dimmable




- Replicates a halogen reflector
- LED positioned further back for anti-glare
- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Equivalent to 25W GU10 Halogen Lamp
- Lifetime of 25,000
- Cree LED Chip

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
REAL MR8 WARM	3W	3000K	210	70	35°	80	MR8	Yes
REAL MR8 COOL	3W	4000K	210	70	35°	80	MR8	Yes

LED MR8 3W 35°

m	35°	lux
1	0.51	392
2	1.03	98
3	1.54	43
4	2.05	24
5	2.57	15



REALITY

R7S 8W Dimmable




- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Equivalent to 75W Halogen Lamp
- Lifetime of 25,000
- Cree LED CHIP

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
LEDTHL 8W 3K 118	8W	3000K	750	94	80°	80	R7s	Yes

LED R7S 8W 80°

m	80°	lux
1	1.66	423
2	3.33	105
3	4.99	47
4	6.66	26
5	8.32	16



PROREALITY

LED LAMPS

The Pro Reality ranges high CRI makes it ideal for lighting interiors, with its superior light bringing out all the colours, materials and textures of the home. The perfect colour spectrum of the light also makes the lamps ideal for lighting artwork and ornaments.

The Pro Reality lamps crisp, superior light is perfect for lighting retail displays, food, cuisine and art. Retail lighting requires perfect colour render



The perfect colour spectrum brings out the vividness of the colours and the clean light brings out the contrast. The Pro Reality lamps will showcase products, food or art at its very best creating the best visual experience.

The Pro Reality range is designed to match a halogen lamp in terms of light source and aesthetics. We achieved this by using a sin

gle Cree LED chip and building the reflector around it. They are our most powerful LED lamps yet, but with the benefit of being energy efficient, all complying to the 2013 Part L regulations. The Lamps high lumen output make them ideal for lighting large spaces and high ceilings.





PRO REALITY

GU10 9W

Dimmable

- Replicates halogen reflector
- Colour Rendering Index of 93
- LED positioned further back for anti glare
- Complies with 2013 Part L regulations
- Fully dimmable with leading & trailing edge dimmers
- Equivalent to 100W Halogen
- Fits 50mm Downlight
- Cree LED CHIP


Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
PRO REALGU1010D3	9W	3000K	800	89	10°	93	GU10	Yes
PRO REALGU1010D4	9W	4000K	800	89	10°	93	GU10	Yes
PRO REALGU1024D3	9W	3000K	800	89	24°	93	GU10	Yes
PRO REALGU1024D4	9W	4000K	800	89	24°	93	GU10	Yes
PRO REALGU1045D3	9W	3000K	800	89	45°	93	GU10	Yes
PRO REALGU1045D4	9W	4000K	800	89	45°	93	GU10	Yes

LED GU10 9W 10°

m	12°	lux 800lm
1	0.19	9157
2	0.8	2289
3	0.57	1017
4	0.76	572
5	0.95	366

LED GU10 9W 45°

m	45°	lux 800lm
1	0.45	2663
2	0.90	665
3	1.36	295
4	1.81	166
5	2.26	106



PRO REALITY

GU10 5W

Dimmable




- Replicates halogen reflector
- Colour Rendering Index of 93
- LED positioned further back for anti glare
- Complies with 2013 Part L regulations
- Fully dimmable with leading & trailing edge dimmers
- Equivalent to 50W GU10
- Fits GU10 lampholder
- Emergency option available
- Cree LED CHIP

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
PRO RETRO5 I45D	5W	2700K	470	93	45°	93	GU10	Yes
PRO RETRO5 W45D	5W	3000K	470	93	45°	93	GU10	Yes
PRO RETRO5 C45D	5W	4000K	470	93	45°	93	GU10	Yes

LED GU10 5W 45°

m	45°	lux
1	0.83	978
2	1.66	237
3	2.49	105
4	3.31	58
5	4.14	37



PRO REALITY

GU10 7W

Dimmable



- Replicates halogen reflector
- Colour Rendering Index of 93
- LED positioned further back for anti glare
- Complies with 2013 Part L regulations
- Fully dimmable with leading & trailing edge dimmers
- Equivalent to 100W Halogen
- Fits 50mm Downlight
- LED Chip 10° : CREE MHD-G 7070 chip
- LED Chip 45° : CREE CXA1820 chip


Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
PRO REAL MR1610D	9W	3000K	800	89	10°	93	MR16	Yes
PRO REAL MR1645D	9W	3000K	800	89	45°	93	MR16	Yes

LED MR16 9W 10°

m	12°	lux
		800lm
1	0.20	8166
2	0.41	2041
3	0.61	907
4	0.82	510
5	1.02	326

LED MR16 9W 45°

m	45°	lux
		800lm
1	0.52	2345
2	1.03	586
3	1.55	260
4	2.07	146
5	2.58	93





PRO REALITY

PAR30 12W

Dimmable

- Replicates halogen reflector
- Colour Rendering Index of 93
- LED positioned further back for anti glare
- Complies with 2013 Part L regulations
- Fully dimmable with leading & trailing edge dimmers
- Equivalent to 75W Halogen
- Fits 50mm Downlight
- LED Chip 15° : CREE CXA1512
- LED Chip 35° : NICHIA 757


Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
PRO REALPAR3015D	12W	3000K	850	71	15°	93	E27	Yes
PRO REALPAR3035D	12W	3000K	850	71	35°	93	E27	Yes

LED PAR30 12W 15°

m	12°	lux 850lm
1	0.18	8410
2	0.35	2102
3	0.71	934
4	0.89	525
5	1.06	336

LED PAR30 12W 35°

m	35°	lux 850lm
1	0.36	4251
2	0.71	1062
3	1.07	472
4	1.42	265
5	1.78	170



PRO REALITY

MODULE 50 10W

Dimmable



- Replicates halogen reflector
- Colour Rendering Index of 93
- LED positioned further back for anti glare
- Complies with 2013 Part L regulations
- Fully dimmable with leading & trailing edge dimmers
- Equivalent to 150W Halogen
- Estimated lifetime of 25,000 hours
- Fits 50mm Downlight
- LED Chip 10° : CREE MHD-G 7070 chip
- LED Chip 45° : CREE CXA1820 chip


Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
PRO REAL50MO/10D	15W	3000K	1400	93	10°	93	-	Yes
PRO REAL50MO/45D	15W	3000K	1400	93	45°	93	-	Yes

LED MODULE 15W 10°

m	10°	lux
1	0.28	4468
2	0.55	1240
3	0.83	562
4	1.11	364
5	1.39	206

LED MODULE 15W 45°

m	45°	lux
1	0.49	1785
2	0.98	496
3	1.48	175
4	1.97	105
5	2.46	69





PRO REALITY

MODULE 35 8W

Dimmable


- Replicates a halogen reflector
- LED positioned further back for anti-glare
- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Equivalent to 75W GU10 Halogen Lamp
- Lifetime of 25,000
- Emergency option available
- Cree XLamp CXA1512 LED

PRO REALITY

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
PRO REAL35MO/35D	8W	3000K	700	88	35°	93	-	Yes

LED MODULE 8W 35°

m	24°	lux
1	0.46	2435
2	0.92	597
3	1.37	280
4	1.83	158
5	2.29	100





REALITY ATMOSPHERE LED LAMPS

The Reality Atmosphere range of lamps emit a warmer light as you dim, to create a more relaxing ambience. the effect known as Warm Dimming does not have anything to do with the actual heat or physical warmth of the bulb, it is when an LED bulb's colour temperature lowers when dimmed.

The lower the brightness the warmer the colour. This is a natural replication since at sunset the sky appears more warm in color,




which puts our minds in a different gear and helps transition us to the night-time. Many incandescent and halogen bulbs naturally have this effect, yet are inefficient. When the Reality Atmosphere Lamps dim, they retain their high efficiency, yet still produce the relaxing and comforting feel of an appealing “warmer” glow.


The Reality Atmosphere lamps also have a high CRI makes it ideal for lighting interi

ors, with its superior light bringing out all the colours, materials and textures of the home. The perfect colour spectrum of the light also makes the lamps ideal for lighting artwork and ornaments.

The Reality Atmosphere range is designed to match a halogen lamp in terms of light source and aesthetics. We achieved this by using a single LED chip and building the reflector around it.



Reality Atmosphere
Full Brightness



Reality Atmosphere
Dimmed



REALITY ATMOSPHERE

GU10 7W

Dimmable

- Dim to Warm 3000K - 2000K
- 85% Energy Savings
- Long lifespan
- High lumen output
- High Colour Rendering Index
- Anti-Glare
- Part L compliant
- Dimmable - compatible with leading/trailing edge dimmers




ATMOSPHERE

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
3/2 REAL GU10/8W	8W	3000K - 2000K	540	68	45°	95	GU10	Yes

LED GU10 8W 45°

m	45°	lux
1	0.72	1001
2	1.44	250
3	2.17	111
4	2.89	62
5	3.61	40





REALITY ATMOSPHERE

GU10 5W

Dimmable




- Dim to Warm 3000K - 2800K
- 85% Energy Savings
- Long lifespan
- High lumen output
- High Colour Rendering Index
- Anti-Glare
- Part L compliant
- Dimmable - compatible with leading/trailing edge dimmers

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
3/2 REAL RETRO5W	5W	2800K - 2000K	400	80	45°	95	GU10	Yes

LED GU10 5W 45°

m	45°	lux 400lm
1	0.78	612
2	1.56	153
3	2.34	68
4	3.12	38
5	3.89	24





REALITY ATMOSPHERE

GU10 7W

Dimmable


- Dim to Warm 3000K - 2000K
- 85% Energy Savings
- Long lifespan
- High lumen output
- High Colour Rendering Index
- Anti-Glare
- Part L compliant
- Dimmable - compatible with leading/trailing edge dimmers



Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
3/2 REAL MR16 8W	8W	3000K - 2000K	540	68	45°	95	GU5.3	Yes

LED MR16 8W 45°

m	45°	lux
1	0.72	1001
2	1.44	250
3	2.17	111
4	2.89	62
5	3.61	40





REALITY ATMOSPHERE

GU10 7W

Dimmable




- Dim to Warm 3000K - 2000K
- 85% Energy Savings
- Long lifespan
- High lumen output
- High Colour Rendering Index
- Anti-Glare
- Part L compliant
- Dimmable - compatible with leading/trailing edge dimmers

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
3/2 REAL AR70D	8W	3000K - 2000K	480	60	35°	95	SBC	Yes

LED AR70 8W 35°

m	35°	lux 480lm
1	0.61	1009
2	1.21	252
3	1.82	112
4	2.42	63
5	3.03	40





REALITY ATMOSPHERE

AR111 12W

Dimmable




- Dim to Warm 3000K - 2000K
- 85% Energy Savings
- Long lifespan
- High lumen output
- High Colour Rendering Index
- Anti-Glare
- Part L compliant
- Dimmable - compatible with leading/trailing edge dimmers

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
3/2 REAL AR111D	12W	3000K - 2000K	628	52	35°	95	G53	Yes

LED GU10 7W 45°

m	45°	lux 630lm
1	0.40	1649
2	0.81	412
3	1.21	183
4	1.61	103
5	2.02	65




LED CONTRACT

ENCLOSED FITTING LAMPS

Our LED Contract lamps are ideal for use in enclosed fittings, such as exterior fittings. This is due to them being constructed from aluminium, which keeps the lamps from overheating when enclosed.

There is also single colour LED GU10 lamps, which are ideal for creating different moods and effects in outdoor or indoor areas.



LED CONTRACT

GU10 6W

Dimmable



- 85% Energy Savings
- Low Carbon Footprint
- High Power 6 in 1 lens LED Technology
- Same size and direct replacement as GU10 Lamp


Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
PUPPYDIMGU1024D	6W	3000K	420	70	24°	80	GU10	Yes
PUPPYDIMGU1045D	6W	3000K	420	70	45°	80	GU10	Yes

LED GU10 6W 24°

m	24°	lux 420lm
1	0.42	1560
2	1.83	395
3	1.25	180
4	1.66	100
5	2.07	66

LED GU10 6W 45°

m	45°	lux 420lm
1	0.83	681
2	1.66	173
3	2.49	95
4	3.31	42
5	4.14	26



LED CONTRACT


GU10 6W

Dimmable Single Colour

- Fully dimmable with leading edge dimmers
- Equivalent to 50W GU10
- Fits GU10 lampholder



Product Code	Wattage	Colour	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
LEDGU107 45D AMB	7W	Amber	290	41	45°	80	GU10	Yes
LEDGU107 45D BLU	7W	Blue	290	41	45°	80	GU10	Yes
LEDGU107 45D GRN	7W	Green	290	41	45°	80	GU10	Yes
LEDGU107 45D RED	7W	Red	290	41	45°	80	GU10	Yes



LED GLASS

DIMMABLE LED LAMPS

Glass Dimmable retrofit lamps featuring a full glass body to mimic exact shape and size as a halogen GU10 lamp but featuring the latest low energy LED technology. 25,000 hours estimated life.





LED GLASS

GU10 5W


Dimmable

- Full glass body
- Suitable for fire rated downlights and dimmable.
- Complies with Part L regulations
- Compatible with a range of leading edge dimmers.
- Equivalent to 50W GU10 Halogen Lamp
- Lifetime of 25,000
- Emergency option available

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
LEDGLGU105WD	5W	3000K	400	80	35°	80	GU10	Yes

LED GU10 5W 35°

m	35°	lux
1	0.64	680
2	1.28	170
3	1.93	75
4	2.57	42
5	3.21	27



Dynamic White

LED MODULES

Lighting changes how we see our surroundings. It can affect our mood, from feeling awake and alert, to relaxed and calm. We're excited to unveil our new Dynamic White Lamps, which gives you the ability to change the colour temperature of your lighting to suite a task or mood.

With Dynamic White Lamps you can adjust the lighting of a room for the various tasks taken within the day.



6500K

4000K

3000K

2700K



Dynamic White




MODULE 8.5W

Dimmable

- Colour temperature adjustable from 2700K - 6500K
- Complies with 2013 Part L regulations
- Fully dimmable with leading edge dimmers
- Equivalent to 75W MR16
- Fits 50mm Downlight

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
DYN MODULE MR16	8.5W	6500K - 2700K	612	72	45°	80	-	Yes



ACCESSORIES

Power Cord 1m 24V	DYNPC1
End Cap 60mm	DYNEND
2M Coupler Lead 24V	DYN2M
5M Coupler Lead 24V	DYN5M
10M Coupler Lead 24V	DYN10M




Dynamic White

MODULE 8.5W 24V

Dimmable

- Colour temperature adjustable from 2700K - 6500K
- Complies with 2013 Part L regulations
- Fully dimmable with leading edge dimmers
- Equivalent to 75W MR16
- Fits 50mm Downlight

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
DYN MODULE MR11	6W	6500K - 2700K	462	77	45°	80	-	Yes



ACCESSORIES

Power Cord 1m 24V	DYNPC1
End Cap 60mm	DYNEND
2M Coupler Lead 24V	DYN2M
5M Coupler Lead 24V	DYN5M
10M Coupler Lead 24V	DYN10M

Dynamic White




AR111 MODULE 12W

Dimmable

- Colour temperature adjustable from 2700K - 6500K
- Complies with 2013 Part L regulations
- Fully dimmable with leading edge dimmers
- Equivalent to 100W AR111
- Fits AR111 Downlight

Product Code	Wattage	Colour Temp	Lumens	Lumens per Watt	Beam angle	CRI	Lamp holder	Dimming
DYN MODULE AR111	12W	6500K - 2700K	1100	92	75°	80	-	Yes



ACCESSORIES

Power Cord 1m 24V	DYNPC1
End Cap 60mm	DYNEND
2M Coupler Lead 24V	DYN2M
5M Coupler Lead 24V	DYN5M
10M Coupler Lead 24V	DYN10M



A. CCT Adjustable Touch Controller 24V

The LED CCT Adjustable Panel Controller is a touch panel glass colour temperature adjustable controller. It adopts a high precision touch control chip that increases touch sensitivity.



- Output: Two channels 96W per channel at 24V
- Connection mode: Common anode
- Supply voltage: DC12-24V
- Static power consumption: <1W
- Output current: <4A (each channel)
- Output power: 12V<96W, 24V<192W

Product Code : LEDP CCT DIM




B. CCT Adjustable Remote


The LED CCT Adjustable Panel Remote is a touch colour temperature adjustable remote. It adopts a high precision touch control chip that increases touch sensitivity. Two AAA batteries are required to operate the remote available separately.



Product Code : LEDP CCT REMOTE



- Output control: Two circuits
- Connection mode: Common anode
- Receiving range: 20m
- Control current: 6A/circuit





C. Wise Scene Dynamic White - Dimming Receiver

The Wise Scene Dynamic White Receiver is controlled by wireless switches or by a push-to-make switch. Designed to work in conjunction with the dynamic white LED tape, Lamps and strips it has 2 outputs for the connection of cool white LEDs and a warm white LEDs, allowing you to adjust the temperature of the colour, mixing the output from cool white to warm white. Receiver also has On/Off and dimmer function with built in memory to remember previous setting when switched on.



- Maximum wattage 200W
- Supply voltage: DC12-24V
- 4 Scenes per receiver
- On/Off and dimmer function
- Built in memory

Product Code : WISEDYN STRIP



Wise Intense 7 Button Switch



Wireless switch which works in conjunction with the Wise Scene Dynamic White Receiver, to control your dynamic fittings.

Wise intense switches are surface mounted so can be positioned almost anywhere. They are battery powered and a CR2430 battery is included with each unit.

Product Code : WISE INTENSE7 WH

RGB+WHITE

LED MODULES

The RGB/W LED Module is a dimmable colour changing and white LED lamp that fits most 50mm downlights. This module offers the versatility to be used for general lighting with warm white or colour changing. This is ideal for creating different moods and ambiances in a space.



RGB

3000K



RGB+WARM WHITE




MODULE 8.5W

Dimmable

- Colour Change and Warm White
- Fully dimmable with leading edge dimmers
- Create Mood and ambiances
- Fits 50mm Downlight
- Plug & Play

Product Code	Wattage	Colour Temp	Beam angle	CRI	Lamp holder	Dimming
LEDRGB/W MOD	8.5W	RGB + 3000K	45°	80	-	Yes



ACCESSORIES

Power Cord 1m 24V	RGBWC1
End Cap	RGBW END 24V
2M Coupler Lead 24V	RGBW 2M
5M Coupler Lead 24V	RGBW 5M
10M Coupler Lead 24V	RGBW 10M

DRIVERS

25W 24V Parallel	RS2524
50W 24V Parallel	RS5024
100W 24V Parallel	RS10024
150W 24V Parallel	RS15024

RGB+WARM WHITE


MODULE 8.5W

Dimmable



- Colour Change and Warm White
- Fully dimmable with leading edge dimmers
- Create Mood and ambiances
- Fits 50mm Downlight
- Plug & Play

Product Code	Wattage	Colour Temp	Beam angle	CRI	Lamp holder	Dimming
LEDRGB/W MOD	8.5W	RGB + 3000K	45°	80	-	Yes



ACCESSORIES

Power Cord 1m 24V	RGBWC1
End Cap	RGBW END 24V
2M Coupler Lead 24V	RGBW 2M
5M Coupler Lead 24V	RGBW 5M
10M Coupler Lead 24V	RGBW 10M

DRIVERS

25W 24V Parallel	RS2524
50W 24V Parallel	RS5024
100W 24V Parallel	RS10024
150W 24V Parallel	RS15024


c. Wise Chameleon Colour Change RGBW

The Wise RGBW V2 Master gives you all the colour change facilities of the standard Chameleon, with the inclusion of a fourth channel to work with red, green, blue and white fittings. This allows the ability to have colour change and warm or cool white using just one chameleon pack. It also gives a greater range of shades of colour including pastels to give a more subtle effect.

Caution: The warm white produced by RGB products is not the same as the warm white produced by single coloured products. By mixing the colours to create warm white a hint of Red, Green, or Blue may appear.



Product Code : **WISERGBW V2 M**



Wise Intense 7 Button Switch



Wireless switch which works in conjunction with the Wise Scene Dynamic White Receiver, to control your dynamic fittings.

Wise intense switches are surface mounted so can be positioned almost anywhere. They are battery powered and a CR2430 battery is included with each unit.

Product Code : **WISE INTENSE7 WH**



Available at...

Head Office / Showroom / Trade Counter
19-23 Lydden Road, Wandsworth,
London, SW18 4LT

Showroom / Trade Counter
82-84 New Kings Road, Fulham,
London, SW6 4LU

t : 020 8874 2234 f : 020 8871 2262 e : info@mr-resistor.co.uk



www.mr-resistor.co.uk